



Low Tire Pressure is Dangerous and Wastes Fuel!

This active tire pressure monitoring system starts flashing RED if the tire pressure drops 5 to 10 psi.



The Easiest TPMS to Calibrate and Recalibrate

- Improved Fuel Economy –
 Proper tire inflation can save an estimated 3% to 5% in fuel costs.
- Safety Improper tire pressure has a detrimental effect on handling, braking and control.
- Longer Tire Life According to the D.O.T., 95% of all premature tire wear is caused by underinflation.
- Self-calibrating LED AirGuard Set & Go memorizes pressure when initially installed and can be easily recalibrated by simply removing and reinstalling.
- The AirGuard Set & Go can be used on any commercial vehicle with tire pressure between 20psi and 180psi.
- Battery standby time is 2 years from the date stamped on the LED AirGuard.



DANGER SAFE

Ultra-bright LED allows for visual checks of each tire, even in daylight!





Complies with the NFPA 1901 & 1917 standards for ambulances and fire trucks.

NFPA 1901 & 1917 Standards require that each tire be equipped with a visual indicator or monitoring system that will indicate tire pressure.

No special tools or key required for installation or calibration.







Starts flashing RED if the tire pressure drops 5 to 10 psi.

Helps to keep Trucks & Fleets CSA compliant.

Designed to fit Trucks, Semis, Trailers, Buses, Motorhomes and other Commercial Vehicles!









For Commercial Trucks with 19.5", 22.5" & 24.5" Aluminum Wheels with Round Holes and 22.5" & 24.5" Standard Steel Wheels with Oval Holes



Tire Pressure Monitoring Kit

Includes: LED AirGuard® Set & Go, Inner and Outer Air Valve Extensions, plus Air Valve Extension Stabilizers.

8 Wheel Kit	
Set & Go Model #	Fits Holes
RWTG1236-82	2"
RWTG1236-85	2.5"
RWTG1236-88	2.8"
RWTG1236-830	3" x 4.5"

6 Wheel Kit	
Set & Go Model #	Fits Holes
RWTG1236-62	2"
RWTG1236-65	2.5"
RWTG1236-68	2.8"
RWTG1236-630	3" x 4.5"

10 Wheel Kit	
Set & Go Model #	Fits Holes
RWTG1236-12	2"
RWTG1236-15	2.5"
RWTG1236-18	2.8"
RWTG1236-1030	3" x 4.5"

Valve Stem Stabilizers

Valve Stem Stabilizers help prevent damage to extensions caused by the rubbing of the extension against the wheel.





Valve Stem Stabilizers		
Model #	Stabilizer Type	
RW0020VSB	2" Round for Aluminum Wheels	
RW0025VSB	2.5" Round for Aluminum Wheels	
RW0028VSB	2.8" Round for Aluminum Wheels	
RW0030VSB	3" x 4.5" Oval for Steel Wheels	



Centrifugal force of a rotating wheel will cause the valve stem to rub against the wheel, resulting in wear and eventual failure of the valve stem.

POP Packaging & Displays Available!



Clamshell Package 4 or 6 packs (5" x 8")





TPMS Kits 6-Wheel (5" x 14.5") 8 and 10-Wheel (7" x 19.5")



FAMA ATTER



